This item was submitted to [Loughborough's Research Repository](#) by the author.
Items in Figshare are protected by copyright, with all rights reserved, unless otherwise indicated.

Inorganic profiles of chemical phosphorus removal sludge

PLEASE CITE THE PUBLISHED VERSION

<http://dx.doi.org/10.1680/wama.2010.163.2.65>

PUBLISHER

ICE Publishing

VERSION

VoR (Version of Record)

LICENCE

CC BY-NC-ND 4.0

REPOSITORY RECORD

Carliell-Marquet, Cynthia, Jennifer Smith, Ioannis Oikonomidis, and Andrew D. Wheatley. 2019. "Inorganic Profiles of Chemical Phosphorus Removal Sludge". figshare. <https://hdl.handle.net/2134/15248>.

This item was submitted to Loughborough's Institutional Repository (<https://dspace.lboro.ac.uk/>) by the author and is made available under the following Creative Commons Licence conditions.

For the full text of this licence, please go to:
<http://creativecommons.org/licenses/by-nc-nd/2.5/>

Cynthia Carliell-Marquet
Lecturer, Department of Civil
Engineering, University of
Birmingham, UK

Jennifer Smith
Academic Fellow, Centre for
Water Sciences, Cranfield
University, UK

Ioannis Oikonomidis
formerly at the Department
of Civil Engineering, The
University of Birmingham, UK

Andrew Wheatley
Professor of Water
Engineering, Department of
Civil and Building Engineering,
Loughborough University, UK

Inorganic profiles of chemical phosphorus removal sludge

C. Carliell-Marquet PhD, J. Smith PhD, I. Oikonomidis PhD and A. Wheatley PhD

Iron dosing is commonly used to remove phosphorus from wastewater but little is known about how this changes the distribution of iron, phosphorus, calcium, magnesium and trace metals in activated and digested sludge. This research compared the inorganic profiles of sludge from full-scale processes (activated sludge and anaerobic digestion) with and without iron dosing, with the aim of identifying changes in inorganic distribution resulting from iron dosing. Sludge phosphorus and metals were fractionated using sequential chemical extraction. Bioavailable iron was lower in iron-dosed activated sludge, as was bioavailable phosphorus (6.5 g/kg compared with 1.8 g/kg), with most of the iron and phosphorus bound as iron-hydroxy-phosphates. Similar results were found for anaerobically digested sludge after iron dosing; iron and phosphorus in the sludge increased by 4 and 1.35 times, respectively, but bioavailability was decreased. The ratio of chemical oxygen demand to bioavailable phosphorus in the digester was 840 : 1 after iron dosing. By contrast, calcium, magnesium, copper and zinc were increasingly bioavailable in the digester after iron dosing. The reported changes were linked to the iron content of the sludge; hence the level of iron dosing is key to minimising changes in sludge inorganic profiles.

1. INTRODUCTION

The final effluent from sewage treatment works (STW) is a significant point source of phosphorus (P) into the environment. The EU urban wastewater treatment directive (UWWTD 91/271/EEC) requires all STW with a population equivalent greater than 10 000 to meet discharge consents of 1–2 mg PO₄^{3–}-P/l if discharging into designated nutrient-sensitive waters. Nature conservation legislation can also be used to impose phosphorus consents when STW discharge into protected areas, such as special areas of conservation (EU Habitats Directive 92/43/EEC), regardless of the size of the STW. In the UK it is estimated that, by 2010, 298 STW will remove phosphorus for the UWWTD and 328 to 342 for nature conservation (Mounsey, 2004). The vast majority will use chemical phosphorus removal (CPR).

Chemical phosphorus removal processes are based on the addition of a metal salt to wastewater, causing precipitation of an insoluble phosphate, which is settled out with the wastewater sludge (Yeoman *et al.*, 1988). Currently in the UK,

iron (Fe) salts are those most commonly used for CPR. The iron salts are usually derived from waste products (Kirk *et al.*, 1987).

Iron-dosing can be done at one or a combination of stages in sewage treatment: (a) pre-precipitation, in which ferric salts are added to raw sewage; (b) co-precipitation, in which ferrous salts are commonly dosed into the aeration basin of the activated sludge (AS) process, Fe(II) being oxidised to Fe(III) prior to orthophosphate (PO₄^{3–}) precipitation; and (c) post-precipitation, in which chemicals are added before or after secondary settlement.

The mass of iron required to precipitate 1 mole of phosphorus can be calculated theoretically

In reality, however, the relationship between the metal salt dose and the phosphorus to be removed is not stoichiometric (Fytianos *et al.*, 1998; Jenkins *et al.*, 1971). The extent of precipitation, and the products formed, is a function of temperature, metal salt dose, pH (Singer, 1972; Yeoman *et al.*, 1988), dissolved oxygen and redox potential (Thistleton *et al.*, 2001).

When Fe(III) salts are dosed to wastewater, positively charged polycations are formed, which complex rapidly with PO₄^{3–}-P and soluble organic anions, thus diverting the normal hydrolysis pathway. Destabilisation of negatively charged colloidal contaminants (such as particulate phosphorus or organic matter), and complexation with anionic sites on the floc surface, occurs with the remaining polycations. Precipitation proceeds by aggregation of the different subunits, sweep-flocculating the remaining colloidal anionic matter and eventually coating the floc surfaces. Once the amorphous precipitates (Fe(III) hydroxide and Fe(III)-hydroxy-phosphate) have formed, further adsorption of PO₄^{3–}-P takes place on their surfaces, but at a slower rate. When Fe(II) is used for CPR, it is usually oxidised to Fe(III) and then follows a similar reaction pathway to that described above. At normal aeration levels (DO ≈ 1.5 mg/l), oxidation takes place rapidly and generates Fe(III) in situ (Nielsen, 1996; Straub *et al.*, 2001) prior to PO₄^{3–}-P precipitation.

Iron-dosed CPR sludge will, therefore, contain a mixture of:

- Fe(III)-hydroxy-phosphate complexes (general formula $\text{Fe}_r\text{PO}_4(\text{OH})_{3r-3}$), which act as centres for further precipitation of Fe(III) hydrolysis products; the stoichiometry of the precipitate formed being a consequence of varying pH, PO_4^{3-} -P and iron concentrations (De Haas *et al.*, 2000; Jiang and Graham, 1998; Thistleton *et al.*, 2001, 2002). The proportion of OH^- compared to PO_4^{3-} increases with increasing pH and iron : phosphorus ratio (Fytianos *et al.*, 1998).
- Amorphous Fe(III) hydroxide precipitates to which PO_4^{3-} -P ions are adsorbed (He *et al.*, 1996; Jiang and Graham, 1998; Thistleton *et al.*, 2002; Yeoman *et al.*, 1988).
- Iron-coagulated organic material.

Other metals are also bound up in CPR sludge through co-precipitation or adsorption of soluble or particulate trace metals to Fe(III)-hydroxy-phosphate compounds during CPR. For example, Fe(III) dosing of a primary effluent (75 mg/l) removed 59% of the soluble copper from the influent (Edwards *et al.*, 1997). In another study, the use of lime or alum for CPR was found to 'significantly enhance the removal of lead, copper, trivalent chromium and arsenic' (van Fleet *et al.*, 1974). An additional source of metals in CPR sludge arises from contamination of the dosing chemicals. Some ferric coagulants were found to contain up to 4 mg/l copper and 46–160 mg/l manganese as contaminants (Edwards *et al.*, 1997).

The total phosphorus content of CPR sludge also increases relative to that of an undosed sludge. For example, total phosphorus increased by 49% (416–620 mg/l) and 55% (625–970 mg/l P) in Fe(III)-dosed primary sludge (Edwards *et al.*, 1997; Kirk *et al.*, 1987). Although CPR sludge is phosphorus-rich, the quantity of bioavailable phosphorus might be limited (Kindzierski and Hrudey, 1986) as it is locked up in Fe(III)-hydroxy-phosphates. Iron dosing has been reported to decrease soluble P concentrations by 91% from 35 to 3 mg/l (Malhrota and Parrillo, 1971).

Chemical phosphorus removal can produce three times more sludge (by mass) in comparison to an undosed process (Mainstone *et al.*, 2000), depending on the dosing location (more sludge is generated from pre-precipitation than from co- or post-precipitation (Brett *et al.*, 1997) and the chemical dose (2 : 1 iron : phosphorus is a common dosing ratio in the UK (Pearce P, Thames Water, personal communication, 2006; Smith R, Severn Trent Water, personal communication, 2006).

Chemical phosphorus removal from sludge that is wasted from primary settlement or secondary treatment requires further treatment, the most common sludge stabilisation process being anaerobic digestion. When CPR sludge is fed into the low redox environment of an anaerobic digester, Fe(III) is reduced to Fe(II), in the process releasing phosphorus (Singer, 1972), as shown in equation (2). One investigator (Nielsen, 1996) noted that 'more than 90% of Fe(III) could be reduced to Fe(II) when stored anaerobically for several days'.

2

The briefly soluble Fe(II) and PO_4^{3-} -P would then be most likely to re-precipitate rapidly in digested sludge as ferrous phosphate.

3

Anaerobic digesters treating Fe(III)-rich CPR sludge will, therefore, undergo short periods of high soluble phosphate concentrations before mass re-precipitation reactions take place. As the inorganic balance of an anaerobic digester is usually regulated by sulfide and carbonate anions (Callander and Barford, 1983) it was hypothesised that this could cause widespread changes in metal speciation. Metals could be swept up during phosphate re-precipitation, becoming adsorbed and entrapped within the ferrous phosphate precipitates.

Alternatively, metals might undergo increasing solubility by being released from sulfide or carbonate precipitates due to Fe(II) competition for these anions. The bioavailability of inorganic nutrients required for anaerobic metabolism could be reduced, or the solubility of toxic metals could be increased, as a result of shifting inorganic profiles.

Little is currently known about how CPR processes change the distribution of iron, phosphorus and trace metals in activated and digested sludge. This research compared the inorganic profiles of AS and digested sludge from CPR STW with their undosed counterparts and discusses the potential implications of the observed changes.

The specific objectives were:

- to develop inorganic profiles for iron-dosed AS and for digesters treating iron-dosed CPR sludge, with respect to phosphorus, iron, calcium, magnesium and trace metals
- to assess the impact of iron dosing on metal and phosphorus bioavailability in activated and digested sludge.

2. MATERIALS AND METHODS

2.1. Analytical methods for fractionation of metals and phosphorus in digested sludge

Sequential chemical extractions are used to divide solid phase inorganic material into fractions by means of selective extractions using a sequence of reagents. The sequential chemical extraction methods used for metal and phosphorus fractionation are shown in Tables 1 and 2, respectively. Concentrations of metals and phosphorus extracted were measured using a sequential plasma emission spectrophotometer with an inductively coupled (argon) plasma source. All methods have previously been described in detail (Carliell-Marquet, 2001). Table 3 shows the tentative assignation of metal and phosphorus species to extracted fractions (Carliell-Marquet, 2001).

2.2. Sludge sampling

Generation of inorganic profiles for CPR sludge by sequential chemical extraction was done in three separate investigations:

- Comparison of activated sludge inorganic profiles from 12 full-scale STW (five iron-dosed; seven undosed).
- Iron-dosing a laboratory-scale activated sludge process to

Metal species found in these fractions ^a	Reagent	Concentration	Extraction time	Liquid : solid ratio (ml : g DS)
Exchangeable metals	KNO ₃	1 mol/l, (pH 6.5)	15 h	50 : 1
Adsorbed metals	KF	0.5 mol/l, (pH 6.5)	15 h	80 : 1
Organic-bound metals	Na ₄ P ₂ O ₇	0.1 mol/l, (pH 9.95)	15 h	80 : 1
Carbonate precipitates	EDTA	0.1 mol/l, (pH 4.63)	15 h	80 : 1
Sulfide precipitates	HNO ₃	1.0 mol/l, (pH 0.25)	15 h	50 : 1
Residual metals	Acid digestion (boiling)	4%	Approx. 1 h	Sludge pellet + 1.3 ml conc. HNO ₃ + 2.7 ml conc. HCl

^aThese categories were assigned in the original method (Stover *et al.*, 1976); however, work done since using model compounds to assign metal species to metal fractions showed that metals of interest to this study do not always conform to these categories (Carliell-Marquet, 2001).

Table 1. Successive stages of the metals sequential extraction method (method adapted from Stover *et al.*, 1976).

Phosphorus species found in these fractions ^b	Reagent	Concentration	Time	Liquid : solid ratio (ml : g DS)
Labile P	Deionised water (deoxygenated)	(pH 6.2)	20 min	30 : 0.5
Struvite/CaCO ₃ -P	Acetate buffer	0.1 mol/l (pH 5.2)	45 min	30 : 0.5
	Deionised water		5 min	30 : 0.5
CaCO ₃ -P	Acetate buffer	0.1 mol/l (pH 5.2)	30 min	30 : 0.5
	Deionised water		5 min	30 : 0.5
Fe P; Al P	NaOH SRP ^c	1 mol/l (pH 13.76)	18 h	30 : 0.5
Org P	NaOH (TP-SRP) ^c			
	Deionised water		5 min	30 : 0.5
Ca-P	HCl	0.5 mol/l (pH 0.6)	18 h	30 : 0.5
	Deionised water		5 min	30 : 0.5
Residual P	Acid digestion (boiling)		Approx. 1 h	Sludge pellet + 1.3 ml conc. HNO ₃ + 2.7 ml conc. HCl

^bPhosphorus model compounds were used to identify phosphorus species recovered the fractions (Carliell-Marquet, 2001).
^cThe NaOH extraction is divided into soluble reactive phosphate (SRP), which represents iron- and aluminium-associated phosphorus. The difference between total phosphorus (measured by ICP) and SRP represents the organic phosphorus fraction.

Table 2. Successive stages of the modified phosphorus sequential extraction method (method adapted from Uhlmann *et al.*, 1990).

Metal species (tentative)	Fraction from metal extraction method (Table 1)	Fraction from P extraction method (Table 2)
FePO ₄	HNO ₃ + residual	NaOH (SRP)
Fe ₃ (PO ₄) ₂ .8H ₂ O	EDTA + some Na ₄ P ₂ O ₇	NaOH (SRP)
Fe(III)-hydroxy-P	EDTA + some Na ₄ P ₂ O ₇	NaOH (SRP)
FeCO ₃	EDTA	Acetate (measure Fe)
FeS	Residual + some HNO ₃	
Ca ₃ (PO ₄) ₂	EDTA	HCl
CaHPO ₄	Na ₄ P ₂ O ₇	HCl
CaCO ₃ (+ adsorbed P)	HNO ₃ + EDTA ^d	Acetate (measure Ca)
MgNH ₄ PO ₄ .6H ₂ O (struvite)	Na ₄ P ₂ O ₇	Acetate

^dRecovery of Ca from CaCO₃ (model compound) is in the residual fraction, however, experiments have suggested the formation of a more soluble Ca-carbonate (possibly Ca-Mg-carbonate) in wastewater, that is extracted preferentially in EDTA.

Table 3. Assigning metal species (tentative) to extraction fractions

measure the effect of CPR on sludge characteristics under controlled laboratory conditions.

- (c) Measuring full-scale digested sludge inorganic profiles during start-up of a CPR dosing programme.

2.3. Sampling 12 STW to compare inorganic profiles of iron-dosed and undosed sludges

Twelve STW were sampled; seven undosed and five iron-dosed (ferrous sulfate co-precipitation). The sampling programme has previously been described in more detail (Smith and Carliell-Marquet, 2008). Return activated sludge (RAS) was

collected from all STW during a single 8 h period. Immediately after sampling, the sludge samples were stored in cool boxes and then placed in a refrigerator (5 ± 1°C) for overnight storage. Sequential chemical extraction was carried out in triplicate the following day.

2.4. Simulation of CPR in a laboratory-scale activated sludge process

A laboratory-scale activated sludge process was continuously dosed with ferrous chloride to remove phosphorus. The system has been described previously (Oikonimidis, 2007). Incoming

feed to the plant consisted of synthetic wastewater (polysaccharides, proteins and volatile fatty acids; COD $\approx$ 1000 mg/l), which was balanced with appropriate concentrations of phosphorus, sulfur, nitrogen and bicarbonate. After a control period without chemical addition, ferrous chloride tetrahydrate ($\text{FeCl}_2 \cdot 4\text{H}_2\text{O}$) was dosed continuously into the aeration basin. Based on influent volume, the dose was 25 mg/l as iron.

2.5. Sampling of digested sludge from a full-scale digester during onset of CPR

The CPR at this STW was by pre-precipitation; ferric sulfate being dosed into raw sewage at a molar ratio of 2 : 1 (iron : phosphorus). Two anaerobic digesters (HRT = 22 days; 35–36°C) treated a mixture of iron-dosed primary sludge and humus sludge (75% of the digester feed) plus some sludge imported into the STW for digestion (25%). Samples of digested sludge were taken by way of a draw-off point at the top of the digester. These were delivered to the laboratory, refrigerated and sequentially extracted within 48 h. Sampling of this digester was over a 118 day period at approximately 10 day intervals during start-up of iron dosing at the STW.

3. RESULTS

3.1. Inorganic content of iron-dosed sludge

Iron dosing of activated sludge increased the inorganic content of that sludge and proportionately decreased the volatile solids (VS) content of that sludge. This is shown in Figure 1, with data taken from a laboratory-scale AS continuously dosed with ferrous chloride over a 10 week period.

Figure 1 shows that the non-volatile suspended solids (nVSS) content of the mixed liquor suspended solids (MLSS) was less than 5% before iron dosing, but following iron dosing the nVSS content rose steadily to reach 38% of the total MLSS solids. At the peak of iron dosing, nVSS comprised 18% iron and 4% phosphorus, by weight. In the post-dosing period, iron-rich sludge was slowly wasted from the reactor resulting in a corresponding decline in the nVSS content of the MLSS.

A similar increase in sludge nVSS content from CPR was found

in the survey of 12 STW. The average nVSS content of iron-dosed AS was $35 \pm 4\%$ ($n = 5$), compared to $26 \pm 5\%$ ($n = 7$) for undosed sludge.

As the inorganic content of the AS increased, physical changes occurred. Figure 2 shows the floc structure during the first week of iron dosing (Figure 2b and d) and at the peak of iron dosing (Figure 2a and c) in the laboratory AS plant. As a result of iron dosing, the flocs became more compact (Figure 2a) with a rusty brown coating. When viewed with scanning electron microscopy, the iron-dosed flocs show a smooth, uniform surface (Figure 2c) in comparison to undosed flocs (Figure 2d). Energy dispersive X-ray analysis spectra revealed that the iron content on the surface of heavily coated flocs (Figure 2c) was as high as $36 \pm 4\%$, whereas for undosed flocs this was below 1%.

3.2. Iron fractionation profiles in CPR activated sludge

Figure 3 shows the iron fractionation profiles of RAS sampled from five iron-dosed and seven undosed STW. Individual iron fractions are shown as a percentage of the total iron in the RAS (total iron concentration indicated above each profile). STW 8 had a relatively low total iron content for a CPR sludge (35 g/kg) but this represents a 10-fold increase in iron content of this sludge as a result of CPR, the pre-CPR iron RAS concentration being only 3 g iron/kg total solids (TS). STW 9 to 12 show typical iron-dosed profiles, with an average iron content of 107 g iron/kg TS, in comparison to 13 g iron/kg TS for the undosed STW.

To identify the characteristic profiles of undosed versus iron-dosed RAS, average iron fractionation profiles for undosed ($n = 7$) and iron-dosed sludges ($n = 5$) are shown in Figure 4. Soluble, potassium nitrate (KNO_3) and potassium fluoride (KF) fractions were combined into one fraction, as were the nitric acid and residual fractions. The first fraction in the series (soluble, potassium nitrate and potassium fluoride) represents iron that was readily extracted from the sludge and hence was likely to be biologically available. This fraction was lower in iron-dosed RAS: 0.7% (0.65 g iron/kg) in comparison with 8% (0.87 g iron/kg) in undosed RAS. The sodium tetraphosphosphate ($\text{Na}_4\text{P}_2\text{O}_7$) fraction was proportionately less in the iron-dosed RAS but actually represents 30.5 g iron/kg, in comparison with 6.2 g/kg in undosed sludge. This was the dominant iron fraction in undosed RAS and was likely to consist mainly of

Figure 1. Increase in non-volatile suspended solids (nVSS) content of mixed liquor suspended solids (MLSS) in a iron-dosed laboratory-scale activated sludge process

comparison with 6.2 g/kg in undosed sludge. This was the dominant iron fraction in undosed RAS and was likely to consist mainly of organically bound iron (Stover *et al.*, 1976) and some Fe(III) hydroxide. In iron-dosed RAS, it is suggested that the sodium tetraphosphosphate-extracted iron was solubilised mainly from amorphous, immature Fe(III)-hydroxy-phosphate compounds, with some contribution from Fe(III) hydroxide and organically bound iron. The CPR RAS was dominated by ethylene diamine tetra-acetic acid

Figure 2. AS floc morphology in laboratory-scale AS process before iron dosing (b, d) and at peak of iron accumulation in the sludge (a, c).

Figure 3. Iron fractions as percentage of total iron in RAS from seven undosed and five iron-dosed full-scale STW

(EDTA)-extracted iron, which represents primarily mature (i.e. more resistant to extraction) Fe(III)-hydroxy-phosphate compounds.

3.3. Phosphorus fractionation profiles in CPR activated sludge

Figure 5 shows the average phosphorus fractionation profiles for undosed and iron-dosed RAS from the 12 STW. Soluble

phosphorus, water-extracted phosphorus and acetate-extracted phosphorus were all designated as bioavailable phosphorus. The sodium hydroxide (NaOH) fraction represents phosphorus extracted from iron phosphates (Fe(II) and Fe(III) phosphates and hydroxy-phosphates) and phosphorus extracted from organic sources. The hydrochloric acid plus residual phosphorus fraction represents phosphorus extracted from calcium phosphates. Figure 5 shows that iron-dosed RAS had

Figure 4. Average iron fractionation profiles of undosed RAS and iron-dosed RAS from full-scale STW

Figure 5. Average phosphorus fractionation profiles of undosed RAS and iron-dosed RAS from full-scale STW

less bioavailable phosphorus than undosed RAS (1.8 g/kg in comparison with 6.5 g/kg). Phosphorus fractionation in iron-dosed RAS was dominated by sodium hydroxide-extracted phosphorus. In the undosed RAS, sodium hydroxide-extracted phosphorus was derived mainly from organically bound phosphorus. The calcium phosphate fraction (hydrochloric acid + Res) was comparable for undosed and iron-dosed RAS.

3.4. Calcium and magnesium fractionation profiles in CPR activated sludge

In addition to iron and phosphorus fractionation profiles, profiles were generated for calcium and magnesium. No clear trends could be identified from the survey of 12 STW with

respect to either calcium or magnesium fractionation profiles (results not shown) but a sample of RAS from STW 8 prior to and after 6 months of iron dosing showed an increase in soluble calcium concentrations after iron dosing (1 mg/l to 3.77 mg/l) and a slight decrease in nitric acid (HNO_3)-extracted calcium, which is the fraction most closely associated with calcium phosphates.

3.5. Inorganic fractionation profiles of digested sludge with CPR sludge input

A full-scale anaerobic digester was sampled for 111 days during start-up of CPR at a STW. The digested sludge samples were sequentially extracted to identify phosphorus and metal

fractions. Table 4 shows the digested sludge characteristics from pre-dosing until day 111 of CPR operation, indicating the changing conditions within the digester as a result of digesting CPR sludge. The first noticeable trend was that of increasing alkalinity, from 2685 mg/l prior to iron dosing to an average of 3651 ± 57 mg/l for the last four samples.

As expected the TS of the digested sludge increased as a result of iron dosing of the feed sludge, from 1.94% to $2.62 \pm 0.2\%$ (average of last four samples). The VS content of the digested sludge also increased during CPR sludge digestion; from 0.82 g/100 ml to 1.3 ± 0.09 g/100 ml. The VS also increased as a percentage of TS, being 42% pre-dosing and $50 \pm 1.3\%$ by day 111. This suggests that the digested sludge was not as efficiently stabilised as it was prior to CPR. Ammonia concentrations in the digester also increased from 322 mg/l to 515 ± 17 mg/l, probably as a result of increased organic loading to the digester. This might also be related to a higher protein content in the digester feed sludge resulting from increased protein coagulation through iron dosing the raw sewage.

3.6. Iron fractionation profiles in digested sludge

Figure 6 shows a steady accumulation of iron in the digested sludge from 18 g/kg dried sludge pre-dosing to 72 g/kg by day 111. The pre-dosing iron fractionation profile is dominated by sodium tetrapyrophosphate-extractable iron (35%; 6.4 g/kg), most likely derived from organic material in the sludge. The EDTA fraction constituted 32% (5.8 g iron/kg), most likely representing a mixture of ferrous carbonate (FeCO_3) and ferrous phosphate $\text{Fe}_3(\text{PO}_4)_2$. The nitric acid plus residual fraction, in which ferrous sulfide (FeS) was solubilised, represented 29% of the total iron in the digested sludge, pre-dosing.

As CPR sludge was fed to the digester, sodium tetrapyrophosphate ($\text{Na}_4\text{P}_2\text{O}_7$)-extractable iron in the digested sludge increased from 6.4 g/kg to 26 ± 1.7 g/kg (average of last four samples). This represents an increase in organically bound iron resulting from iron coagulation of raw sewage, and partial recovery of iron from ferrous phosphate. EDTA-extracted iron (representing primarily ferrous phosphate) increased from 5.8 to 41.3 g/kg over the 111 days of CPR sludge digestion. Ferrous carbonate was also recovered in EDTA and to differentiate

Figure 6. Iron fractions showing changing profile of a full-scale anaerobic digester pre- and post-CPR

between ferrous phosphate and carbonate, it is useful to measure iron in the acetate extractions of the phosphorus sequential extraction scheme, where ferrous carbonate was solubilised. This indicated that ferrous carbonate only increased from 1.26 to 3.8 g/kg by day 111, confirming the dominance of ferrous phosphate in the EDTA fraction.

Most interesting is the reduction in nitric acid plus residual extracted iron (i.e. from ferrous sulfide) during CPR. Twenty-nine per cent of the iron pre-dosing was recovered in this fraction (5.2 g/kg), which decreased to 3.6 g/kg by day 111, representing only 5% of the total iron in the digester. Iron is usually the primary regulator of sulfide solubility in an anaerobic digester, so a decrease in the formation of ferrous sulfide could result in higher concentrations of trace metals, such as nickel and cobalt, being precipitated as sulfides in the digested sludge.

These results suggest that iron solubility in the digester pre-CPR was controlled primarily by ferrous sulfide precipitation but that introduction of iron-dosed CPR sludge shifted the balance to ferrous phosphate precipitation, with ferrous sulfide decreasing in importance and ferrous carbonate increasing in importance.

3.7. Phosphorus fractionation profiles in digested sludge

Figure 7 shows the phosphorus profile of the anaerobic digester. Phosphorus in the digester increased in total as a result of CPR, with an average iron : phosphorus ratio in the digested sludge of

	Pre iron dosing	Dosing of primary sludge with ferric sulfate									
		Day 11	Day 18	Day 25	Day 40	Day 49	Day 54	Day 60	Day 97	Day 104	Day 111
pH	7.42	7.8	7.53	7.52	7.35	7.52	7.25	7.44	7.43	7.42	7.49
Alkalinity: mg CaCO ₃ /l	2685	3237	3510	3394	3214	3127	3208	3063	3626	3679	3574
Sulfide: mg/l	2.2	0.27	1.2	1.3	2.6	1.9	1.8	2.3	3.43	3.89	2.1
Ammonia: mg/l	322	350	365	366	336	329	308	no data	507	522	534
TOC _{soluble} : mg/l	969	926	1048	1101	1101	1002	1041	1080	1121	1076	1043
IC _{soluble} : mg/l	462	557	604	584	553	538	552	527	624	633	615
TS: g/100 ml	1.94	2.09	2.47	2.37	2.46	2.16	2.25	2.14	2.33	2.53	2.84
VS: g/100 ml	0.82	0.93	1.13	1.08	1.08	0.95	0.99	0.96	1.2	1.28	1.41
%VS	42.4	44.6	45.7	45.7	43.9	44	44	44.6	51.3	50.4	49.6

Table 4. Characteristics of full-scale digested sludge samples

Figure 7. Phosphorus fractions showing changing profile of a full-scale anaerobic digester pre- and post-CPR

2.24 ± 0.3 by day 111. Digestion of the CPR sludge had an effect on every phosphorus fraction, with all fractions decreasing in both mass and percentage, except for the sodium hydroxide fraction. It should be noted that in Figure 7, the sodium hydroxide fraction has been further divided by differentiating between soluble reactive phosphorus (SRP) (representing phosphorus from inorganic iron phosphates) and non-reactive phosphorus (representing phosphorus from organic material). Sodium hydroxide-extracted SRP increased from 26% (5.6 g/kg) pre-dosing to 64% (21 g/kg) by day 111. By contrast, the hydrochloric acid plus residual P fraction (Ca-P), was reduced from 7.2 to 5.9 g/kg.

Figure 8 shows the more labile phosphorus fractions in the digested sludge. These fractions were rapidly extracted with water and acetate buffer and so were considered to be biologically available. CPR sludge digestion had an immediate

effect on the mass of bioavailable phosphorus in the digester, decreasing it from 3.61 g/kg pre-dosing to 1.65 g/kg by day 111. Moreover, the remaining bioavailable phosphorus is almost entirely represented by the acetate-extractable phosphorus, with the soluble and water phosphorus fractions having decreased by 96% from their pre-dosing levels. The COD : P_{bioavailable} ratio in the digester sludge was 170 : 1 pre-dosing but increased to 840 : 1 by day 111.

3.8. Fractionation profiles of other metals in digested sludge

As well as iron and phosphorus, which are directly involved in the CPR process, other metals were fractionated to identify changes in their profiles. The first noticeable change in the digested sludge was that all metals measured, apart from iron, decreased in terms of their mass per mass of dried sludge over the 111 day period. On average, metals decreased by 39 ± 3%

Figure 8. Bioavailable phosphorus fractions in a full-scale anaerobic digester pre- and post-CPR

from their pre-dosing levels, with the biggest decrease being by calcium (43%) and the smallest by manganese (34%). This is thought to be related primarily to the increase in total solids concentration in the feed and digested sludge (Table 4), as a result of CPR, with non-dosed metals being proportionately less on a weight-for-weight basis.

Calcium is usually an important precipitant of phosphorus in digesters, but the hydrochloric acid-extracted phosphorus (Figure 7) suggested Ca-P had decreased as a result of CPR sludge digestion. This was supported by the calcium extraction profiles, which showed decreasing extraction of calcium from the Ca-P fractions, with a corresponding increase in soluble calcium in the digester (Figure 9).

Magnesium (results not shown) followed a similar trend to calcium, although changes were slower and less pronounced. Soluble magnesium was stable for the first 96 days of CPR at 40 ± 2.5 mg/l but then increased to 52 mg/l by day 111. As for calcium, fractions of magnesium at the upper end of the fractionation profile (residual magnesium, nitric acid and EDTA extractable magnesium), which are likely to represent magnesium phosphate precipitates, decreased.

Trace metals (nickel, copper, zinc, chromium, manganese) were also fractionated using the metals sequential extraction method, the results are presented in Figure 10. Two fractionation profiles are shown for each metal: pre-dosing and day 60 of CPR. With the exception of manganese, all the trace

metals exhibited a shift towards the lower end of the fractionation profiles, suggesting they could be more easily extracted from the sludge post-CPR. Copper is particularly interesting: pre-dosing copper was resistant to extraction, with 63% in the nitric acid and residual fractions, indicating that most copper was present as copper sulphide. Following CPR, copper in the digested sludge shifts towards the sodium tetraphosphosphate ($\text{Na}_4\text{P}_2\text{O}_7$) and EDTA fractions. CPR sludge digestion has the opposite effect on manganese fractionation, with manganese becoming less extractable over the 60 day period, shifting up the fractionation profile to be extracted primarily with EDTA.

4. DISCUSSION

Chemical phosphorus removal has been found to induce changes in metal and phosphorus fractionation in wastewater sludge, with the bioavailability of a number of metals and phosphorus being affected.

The bioavailability of a metal can be defined as the fraction of the total metal in a particular environment that is in a form suitable for uptake by a cell (Turner, 1984). The size of this fraction is important in determining the availability of essential trace nutrients or toxicity of metals. It is difficult to measure and there is little evidence to relate metal speciation and metal bioavailability in wastewater treatment systems (Zandvoort *et al.*, 2006). Sequential chemical extractions give an insight into metal dynamics in wastewater sludges. The chemical extractants are applied in order of increasing aggressivity to divide the metals into fractions that represent their ease of extraction; the most readily extractable being at the beginning of the sequence and the most resistant, for example, the sulfide precipitates, towards the end. Hence, it can be assumed that biological availability of the metal fractions is greatest in the initial fractions and the metals (or phosphorus) become increasingly unavailable as the fractions progress through the sequence (Aquino and Stuckey, 2007; Carliell-Marquet, 2001; Zandvoort *et al.*, 2006).

Soluble metals are considered to be the most readily bioavailable fraction, but most soluble metals in wastewater treatment systems are not free ions in solution; they are complexed with a range of soluble organic ligands and inorganic ions. These metals are, therefore, only bioavailable if the wastewater micro-organisms have a stronger affinity for the metal than the complexing agent (Callander and Barford, 1983). Previous researchers have concluded that precipitated metals are not readily bioavailable to micro-organisms (Aquino and Stuckey, 2007; Callander and Barford, 1983; Gonzalez-Gil *et al.*, 2002; Hoban and van den Berg, 1979; Mosey *et al.*, 1971; Pfeffer and White, 1964; Zandvoort *et al.*, 2006), which corresponds to their resistance to extraction.

It is important to note, however, that metal distribution between soluble and solid phases is a dynamic phenomenon, which changes continually depending on the concentration of each metal in a particular environment and competition between them for adsorption and complexation sites and precipitating anions. Thus precipitated metals are not readily bioavailable but represent a reservoir of metal that could become bioavailable if environmental conditions change (Ginter and Grobicki, 1997; Gonzalez-Gil *et al.*, 2002).

Speciation of metals governs metal toxicity in a similar manner to that of bioavailability, with metal species unavailable to micro-organisms also being rendered less toxic to micro-organisms (Hughes and Poole, 1989; Mehrota *et al.*, 1993; Mosey *et al.*, 1971).

For the metals sequential extraction method (Table 1), bioavailable fractions were designated as the soluble fraction and the fractions containing readily exchangeable metal (potassium nitrate) and adsorbed metal (potassium fluoride). As metal uptake by microbial cells is thought to start with passive adsorption of metal onto the cell surface (Turner, 1984), this seems a good indication of metal bioavailability. The second phase of metal uptake is energy-dependent transport into the cell (Hughes and Poole, 1989), hence the organically bound metal fraction sodium tetraphosphosphate ($\text{Na}_4\text{P}_2\text{O}_7$) could also be representative of metal bioavailability. However, a number of inorganic precipitates also contribute to this fraction by being partially solubilised in sodium tetraphosphosphate ($\text{Na}_4\text{P}_2\text{O}_7$); for this reason the sodium tetraphosphosphate ($\text{Na}_4\text{P}_2\text{O}_7$) fraction has not been included with the bioavailable fractions.

For the phosphorus sequential extraction method (Table 2), bioavailable fractions were designated as the soluble, water- and acetate-extractable fractions. The acetate-extractable fractions do contain phosphorus adsorbed to calcium carbonate or within struvite, but are included because this is a relatively mild extraction for a short time period and hence represents phosphorus from precipitates that are rapidly solubilised under weakly acidic conditions.

The inorganic profiles presented in this study show a general trend of decreasing bioavailability of iron and phosphorus in iron-dosed sludge. Iron bioavailability decreases in both iron-dosed AS and digested sludge. This is a relatively small decrease (870–650 mg/kg in AS and 640–590 mg/kg in digested sludge) but then the initial amount of bioavailable iron was only a small fraction of the total iron, so it is possible that a relatively small change could tip the balance towards that system being iron deficient. Iron is known to be an essential metal for all micro-organisms (Hughes and Poole, 1989) and has been reported to increase AS microbial activity when supplemented to nutrient-deficient systems (Carter and McKinney, 1973; Derco *et al.*, 1998). Iron is particularly important for efficient anaerobic metabolism (Callander and Barford, 1983; Hoban and van den Berg, 1979; Pfeffer and White, 1964) and has been found to increase biogas production significantly when supplemented to anaerobic digesters with low bioavailable iron concentrations.

Decreasing bioavailable phosphorus (Figures 5, 7 and 8) is an obvious outcome of CPR, when the intention is to precipitate phosphorus. A marked reduction in the amount of soluble and water-extractable phosphorus was found in iron-dosed AS (2.9–0.7 g/kg) as well as acetate-extractable phosphorus. Aerobic treatment systems have well established COD : nitrogen : phosphorus requirements (100 : 5 : 1) and it is possible that iron dosing could reduce bioavailable phosphorus below this level.

Reduction of bioavailable phosphorus was even more extreme

in the anaerobic digester (Figure 8), resulting in no measurable soluble phosphorus and very little water- or acetate-extractable phosphorus (2.63–0.83 g/kg); decreasing phosphorus bioavailability being clearly linked to the input of iron-dosed primary sludge to the digester. Anaerobic digesters, like all biological systems, are known to require phosphorus although exactly how much has not been established. A COD : phosphorus ratio of 125 : 1 has previously been recommended for anaerobic sludge digesters (Jack *et al.*, 1976). This digester had a pre-dosing COD : $P_{\text{bioavailable}}$ ratio of 170 : 1, which increased to 840 : 1 post-CPR. It seems likely that, if these conditions were sustained, this digester would become phosphorus deficient, which could lead to slower rates of acetate utilisation and a reduction in methane output (Alphenaar *et al.*, 1993). This needs to be taken into account when developing a CPR dosing programme for a STW, as optimising the iron dose might not only be an important factor in reducing chemical costs for CPR but might also be critical in ensuring a minimum level of bioavailable phosphorus in the digesters, which is in turn important to ensure steady biogas production.

Chemical phosphorus removal sludge digestion actually increased the bioavailability of metals such as calcium, magnesium, copper and zinc. Calcium solubility in digested sludge increased when iron-dosed primary sludge was fed to the digester, as a result of decreased calcium phosphate precipitation. Calculating the free Ca^{2+} concentration in equilibrium with orthophosphate (PO_4^{3-}) or carbonate (CO_3^{2-}) ($K_{\text{sp}} = 10^{-6.7}$ for calcium carbonate in wastewater (Loewenthal, 1997) showed that calcium solubility in the digester was controlled by phosphate precipitation prior to iron dosing. Post-CPR sludge digestion, with soluble phosphorus less than 0.05 mg/l, calcium solubility was controlled primarily by carbonate precipitation, thus increasing soluble calcium concentrations. A consequence of increased calcium and magnesium solubility in wastewater is likely to be a greater incidence of pipework scaling by calcium carbonate or calcium magnesium carbonate (Ca-Mg-CO_3) precipitates, particularly if the trend towards increasing alkalinity in the digester is also taken into account. This likelihood is further exacerbated by the lack of soluble orthophosphate in the wastewater, which acts as an inhibitor for calcium precipitation.

Both copper and zinc in digested sludge (Figure 10) moved down the fractionation profiles after CPR sludge digestion, although this did not alter the designated bioavailable fractions. It seems that copper in particular was less strongly precipitated with sulfide than before CPR. Both metals showed an increase in the sodium tetrapyrophosphate ($\text{Na}_4\text{P}_2\text{O}_7$) fraction, which could represent increasing concentrations of copper and zinc in microbial cells. In previous work, increasing sodium tetrapyrophosphate-extracted copper was found to be indicative of digester deactivation (Hayes and Theis, 1978; Mehrota *et al.*, 1993), due to copper build-up in the biomass fraction. Thus, CPR sludge digestion could mobilise metals such as copper and zinc that are traditionally strongly precipitated as sulfides. The reason for this is unclear; intuitively it would seem that increasing iron concentrations in the digester could limit sulfide availability for precipitation with trace metals; however, iron fractionation profiles suggested lower ferrous sulfide concentrations in the digester post-CPR and soluble

sulfide measurements also increased post-CPR. It is also possible that copper and zinc were caught up in the ferrous phosphate re-precipitation reactions, becoming adsorbed to or entrapped within the precipitates and then being released in the sodium tetrapyrophosphate ($\text{Na}_4\text{P}_2\text{O}_7$) fraction. This certainly occurred with manganese, which was extensively co-precipitated with ferrous phosphate and recovered in the EDTA fraction. Manganese is an essential trace metal, particularly important for the acidogenic bacteria in anaerobic digestion (Hughes and Poole, 1989). Thus reducing manganese bioavailability could have a negative effect on anaerobic digestion and consequently, biogas production.

5. CONCLUSIONS AND RECOMMENDATIONS

- Iron dosing for CPR alters the solubility and bioavailability of iron, phosphorus and trace metals in activated and digested sludge.
- Iron-dosed AS contained on average eight times the mass of iron and 1.5 times the mass of phosphorus found in undosed AS. Iron and phosphorus are most likely bound up as Fe(III)-hydroxy-phosphate and are unlikely to be biologically available.
- The bioavailable phosphorus fraction in iron-dosed AS was on average only 28% of that found in undosed AS. This implies that iron dosing could cause phosphorus limitation in AS under conditions of high dosing. More work is needed to understand the relationship between the nutrient requirements of AS and nutrient bioavailability.
- CPR sludge fed to anaerobic digesters will result in phosphorus being re-precipitated as ferrous phosphate within the digested sludge. This is likely to reduce phosphorus bioavailability in the digesters. In this study it was reduced to 30% of pre-dosing levels. Hence, phosphorus bioavailability could become a limiting factor for digesters treating high proportions of iron-dosed sludge and further work is needed to establish the conditions under which this might occur.
- Anaerobic digestion of CPR sludge resulted in other metals (calcium, magnesium, copper, chromium, zinc, nickel) being more easily extracted post-dosing, except for manganese which was more resistant to extraction. For calcium this was related to reduced precipitation of calcium phosphates and for the trace metals this was thought to be caused by the metals being caught up in the ferrous phosphate re-precipitation reactions, instead of being precipitated as metal sulfides or carbonates. This is likely to increase the biological uptake of these trace metals, which could be beneficial or inhibitory depending on the metal and the concentrations involved. More work is needed to further our understanding of metal bioavailability in anaerobic digesters.

ACKNOWLEDGEMENTS

Results used in this paper are from research funded by EPSRC grants GR/K/96946 and GR/R58550/01; and PGTA funding (Department of Civil Engineering, The University of Birmingham).

REFERENCES

Alphenaar PA, Sleyster R, De Reuver P, Ligthart GJ and Lettinga G (1993) Phosphorus requirement in high-rate

- anaerobic wastewater treatment. *Water Research* 27(5): 749–756.
- Aquino SF and Stuckey DC (2007) Bioavailability and toxicity of metal nutrients during anaerobic digestion. *Journal of Environmental Engineering – ASCE* 133(1): 28–35.
- Brett S, Guy J, Morse GK and Lester JN (1997) *Phosphorus Removal and Recovery Technologies*. Selper Publications, London, UK.
- Callander IJ and Barford JP (1983) Precipitation, chelation and the availability of metals as nutrients in anaerobic digestion. I. Methodology. *Biotechnology and Bioengineering* 15(8): 1947–1957.
- Carliell-Marquet CM (2001) *The Effect of Phosphorus Enrichment on Fractionation of Metal and Phosphorus in Anaerobically Digested Sludge*. PhD Thesis, Loughborough University.
- Carter JL and McKinney RE (1973) Effects of iron on activated sludge treatment. *Journal of Environmental Engineering – ASCE* 99(EE2): 135–152.
- De Haas D, Wentzel M and Ekama G (2000) The use of simultaneous chemical precipitation in modified activated sludge systems exhibiting biological excess phosphate removal. Part 1: Literature review. *Water SA* 26(4): 439–451.
- Derco J, Kuffa R, Kusnierova J and Fargasova A (1998) Influence of phosphorus precipitants on activated sludge activity. *Journal of Trace and Microprobe Techniques* 16(4): 417–425.
- Edwards M, Courtney B and Heppler PS (1997) Beneficial discharge of iron coagulation sludge to sewers. *Journal of Environmental Engineering – ASCE* 123(10): 1027–1032.
- Fytianos K, Voudrias E and Raikos N (1998) Modelling of phosphorus removal from aqueous and wastewater samples using ferric iron. *Environmental Pollution* 101(1): 123–130.
- Ginter MO and Grobicki AM (1997) Manganese removal mechanisms in a stirred UASB reactor. *Water Research* 31(6): 1261–1268.
- Gonzalez-Gil G, Jansen S, Zandvoort MH and van Leeuwen HP (2002) Effect of yeast extract on speciation and bioavailability of nickel and cobalt in anaerobic digesters. *Biotechnology and Bioengineering* 82(2): 134–142.
- Hayes TD and Theis TL (1978) The distribution of heavy metals in anaerobic digestion. *Journal of the Water Pollution Control Federation* 50(1): 61–72.
- He Q, Leppard G, Paige C and Snodgrass W (1996) Transmission electron microscopy of a phosphate effect on the colloid structure of iron hydroxide. *Water Research* 30(6): 1345–1352.
- Hoban DJ and van den Berg L (1979) Effect of iron on conversion of acetic acid to methane during methanogenic fermentation. *Journal of Applied Bacteriology* 47(1): 153–159.
- Hughes MN and Poole RK (1989) *Metals and Microorganisms*. Chapman and Hall, London.
- Jack ME, Farquhar GJ and Cornwall GM (1976) Anaerobic digestion of primary sludge containing iron phosphate. *Water Pollution Research in Canada* 8: 91–109.
- Jenkins D, Ferguson JF and Menar AB (1971) Chemical processes for phosphate removal. *Water Research* 5(7): 369–387.
- Jiang J and Graham N (1998) Pre-polymerised inorganic coagulants and phosphorus removal by coagulation – a review. *Water SA* 24(3): 237–244.
- Kindzierski W and Hrudey S (1986) Effects of phosphorus removal chemicals upon methane production during anaerobic sludge digestion. *Canadian Journal of Civil Engineering* 31(1): 33–38.
- Kirk PW, Hunter M, Lester JN and Perry R (1987) Chemically assisted phosphorus precipitation: effects on anaerobic digestion and AERCON sludge thickening. *Environmental Technology Letters* 8(11): 545–554.
- Loewenthal RE (1997) *The Application of Chemical Equilibrium to the Control of Struvite and Calcite Precipitation in Waste Water Treatment*. Water Research Commission (South Africa) Report No. 602/1/97.
- Mainstone C, Parr W and Day M (2000) *Phosphorus and River Ecology – Tackling Sewage Inputs*. English Nature/Environment Agency Report, March 2000, UK.
- Malhrota SK and Parrillo TP (1971) Anaerobic digestion of sludges containing iron phosphates. *Journal of the Sanitary Engineering Division, Proceedings of the American Society of Civil Engineers*, 97(5): 629–645.
- Mehrota A, Mehrota I and Tandon SN (1993) Role of Cu (II) and Zn (II) species on the anaerobic digestion of synthetic activated sludge. *Journal of Chemical Technology and Biotechnology* 56(2): 185–190.
- Mosey FE, Swanwick JD and Hughes DA (1971) Factors affecting the availability of heavy metals to inhibit anaerobic digestion. *Water Pollution Control* 70(6): 668–679.
- Mounsey S (2004) Public considerations for sustainable phosphorus removal. *Proceedings of CIWEM Conference Phosphorus Removal from Wastewaters: Still a Problem in the UK*. Leeds, CIWEM, UK.
- Nielsen PH (1996) The significance of microbial Fe(III) reduction in the activated sludge process. *Water Science and Technology* 37(4–5): 403–406.
- Oikonomidis I (2007) *Iron Accumulation in Activated Sludge as a Result of Chemical Phosphorus Removal – Effect on Floc Properties and Biological Activity*. PhD thesis, The University of Birmingham.
- Pfeffer JT and White JE (1964) The role of iron in anaerobic digestion. *Proceedings of 19th Industrial Waste Conference*, Purdue University Press, USA. pp. 887–901.
- Singer PC (1972) Anaerobic control of phosphate by ferrous iron. *Journal of the Water Pollution Control Federation* 44(4): 663–669.
- Smith JA and Carliell-Marquet CM (2008) The digestibility of iron-dosed sludge. *Bioresource Technology* 99(18): 8585–8592.
- Stover RC, Sommers LE and Silveira DJ (1976) Evaluation of metals in wastewater sludge. *Journal of the Water Pollution Control Federation* 48(9): 2165–2175.
- Straub K, Benz M and Schink B (2001) Iron metabolism in anoxic environments at near neutral pH. *FEMS Microbiology Ecology* 34(3): 181–186.
- Thistleton J, Clark T, Pearce P and Parsons S (2001) Mechanisms of chemical phosphorus removal 1 – Iron (II) salts. *Transactions of the Institution of Chemical Engineers* 79(B): 339–344.
- Thistleton J, Berry TA, Pearce P and Parsons S (2002) Mechanisms of chemical phosphorus removal 2 – Iron (III) salts. *Transactions of the Institution of Chemical Engineers* 80(B): 265–269.

- Turner DR (1984) Relationships between biological availability and chemical measurements. In *Metal Ions in Biological Systems, Vol. 18: Circulation of Metals in the Environment* (Sigel H (ed.)). Marcel Dekker, New York, pp. 137–164.
- Uhlmann D, Roske I, Hupfer M and Ohms G (1990) A simple method to distinguish between polyphosphate and other phosphate fractions of activated sludge. *Water Research* 24(11): 1355–1360.
- van Fleet G, Barr J and Harris A (1974) Treatment and disposal of chemical phosphate sludge in Ontario. *Journal of the Water Pollution Control Federation* 46(3): 582–587.
- Yeoman S, Stephenson T, Lester JN and Perry R (1988) The removal of phosphorus during wastewater treatment: a review. *Environmental Pollution* 49(3): 183–233.
- Zandvoort MH, Van Hullebusch ED, Feroso FG and Lens PN (2006) Trace metals in anaerobic granular sludge reactors: bioavailability and dosing strategies. *Engineering Life Science* 6(3): 293–301.

What do you think?

To discuss this paper, please email up to 500 words to the editor at journals@ice.org.uk. Your contribution will be forwarded to the author(s) for a reply and, if considered appropriate by the editorial panel, will be published as discussion in a future issue of the journal.

Proceedings journals rely entirely on contributions sent in by civil engineering professionals, academics and students. Papers should be 2000–5000 words long (briefing papers should be 1000–2000 words long), with adequate illustrations and references. You can submit your paper online via www.icevirtuallibrary.com/content/journals, where you will also find detailed author guidelines.